

BC Geo textile

SECTION 1:

Identification of the substance/mixture and of the company/undertaking

1.1.Product identifier

Product name BC Geo textile

Product Use: Construction

Building Chemistry Industry

P.Code 338941

Tel: 0138050533

Mob: 0593120221

Kingdom of Saudi Arabia

Emergency telephone+0593120221 966

SECTION 2:

Hazards identification

SECTION 3:

This substance is NOT hazardous according to the Hazardous Substances (Classification)

| Ingredients | Wt% | CAS NUMBER. |
|---|----------|-------------|
| Poly(oxy-1,2-ethanediyloxycarbonyl-1,4-phenylenecarbonyl) | 90-100 % | 25038-59-9 |
| Graphite | 1-<5 % | 7782-42-5 |
| Titanium dioxide | 0-<1 % | 13463-67-7 |
| Carbon Black | 0-<1 % | 1333-86-4 |



SECTION 4:

If in Eyes:

Rinse cautiously with water for 15 minutes. If eye irritation persists: Get medical advice.

If on Skin:

Wash with plenty of soap and water. If skin irritation occurs: get medical advice/attention.

If Swallowed:

DO NOT induce vomiting. Wash out mouth thoroughly with water. Never give anything to the mouth of an unconscious person. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Seek medical attention if needed.

If Inhaled:

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

SECTION 5:

Firefighting measures

| | |
|---|---|
| Hazard Type | This product will burn if exposed to fire. |
| Hazards from combustion products | Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen. |
| Suitable Extinguishing media | Carbon dioxide, dry powder, chemical foam. |
| Precautions for firefighters and special protective clothing | Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses. |
| HAZCHEM CODE | None Allocated |



SECTION 6:

Accidental release measures

Remove all sources of ignition. Increase ventilation. Evacuate all unprotected personnel. Do not breathe loose fiber. Wear respiratory protection and full protective clothing to minimise exposure. Sweep up material avoiding loose fiber generation -dampen spilled material with water if suitable to avoid airborne loose fiber, OR where possible use dustless methods such as vacuum to collect the material; then transfer material in to suitable vapour tight labelled containers for subsequent recycling or disposal. Dispose of waste according to applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

SECTION 7:

Handling and storage

Precautions for Handling:

- Avoid inhalation of loose fibre, and skin or eye contact. Use only in a well-ventilated area.
- Keep containers sealed when not in use.
- Prevent the build-up of loose fibre in the work atmosphere.
- Establish good housekeeping practices.
- Remove loose-fibre accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating loose fibre.
- Maintain high standards of personal hygiene i.e. washing hands prior to eating, drinking, smoking or using toilet facilities.

Precautions for Storage:

- Store in a well-ventilated area away from heat and sources of ignition, out of direct sunlight and moisture.
- Take precautions against static electricity discharges.
- Use proper grounding procedures.
- Store away from incompatible materials such as materials that support combustion (oxidising materials).
- Store in suitable, labelled containers.
- Inspect periodically for deficiencies such as damage or leaks.
- Have appropriate fire extinguishers available in and near the storage area.
- Ensure that storage conditions comply with applicable local and national regulations

Building Chemistry Industry

Suit No 203, Al Manar Business park Bin Khalid Street Dammam .Kingdom of Saudi Arabia.

Email: info@bcisaudi.com Website: www.bcisaudi.com



SECTION 8:

Exposure Controls/personal protection

| | TWA | STEL | | |
|-----------|-----|-------|-----|-------|
| Substance | ppm | mg/m3 | ppm | mg/m3 |

Graphite, all forms except graphite fibers [5-42-7782] 3(r)

Titanium dioxide [7-67-13463] 10

Carbon black 6.7B [4-86-1333] 3

Workplace Exposure Standard – Time Weighted Average (WES-TWA).The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

Engineering Controls:

Use with good general ventilation. A flameproof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of particulates/fibres below the exposure standards, suitable respiratory protection must be worn.

Personal Protection Equipment:


| | |
|--------------------|---|
| Eyes | Safety glasses with side shields, full face shield or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 2 & 6 (2012) - Eye Protectors for Industrial Applications. |
| Skin | Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1 (2016): Occupational protective gloves - Selection, use and maintenance. Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled. |
| Respiratory | If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable dust/ particulate/fiber filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715 (2009), Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716 (2012), Respiratory Protective Devices, in order to make any necessary changes for individual circumstances. |

Building Chemistry Industry

Suit No 203, Al Manar Business park Bin Khalid Street Dammam .Kingdom of Saudi Arabia.

Email: info@bcisaudi.com Website: www.bcisaudi.com





SECTION 9:

Physical and Chemical Properties

| |
|--|
| State: Liquid |
| Colour: Black |
| Odour: Aromatic |
| Evaporation rate: Moderate |
| Oxidising: Non-oxidising (by EC criteria) |
| Solubility in water: Insoluble |
| Also soluble in: Most organic solvents. |
| Viscosity: Non-viscous |
| Boiling point/range°C: 153 Flammability limits %: lower: No data available. |
| upper: No data available. Flash point°C: 39 |
| Part.coeff. n-octanol/water: No data available. Autoflammability°C: No data available. |
| Relative density: 0.916 pH: Approx. 7 |
| VOC g/l: 450 |



| | |
|----------------------------------|---------------|
| Explosive Limits | |
| Vapour Pressure | Not available |
| Vapour Density | Not available |
| Specific Gravity | Not available |
| Water Solubility | Not available |
| Partition Coefficient: | Not available |
| Auto-ignition Temperature | Not available |
| Decomposition Temperature | Not available |
| Kinematic Viscosity | Not available |
| Particle Characteristics | Not available |

SECTION 10:

Stability and reactivity

| | |
|---|--|
| Stability of Substance | This product is stable under normal conditions. |
| Possibility of hazardous reactions | Reacts with incompatible materials. |
| Conditions to Avoid | Dust accumulation, heat and other sources of ignition. |
| Incompatible Materials | Strong oxidising agents. |
| Hazardous Decomposition Products | Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen. |

SECTION 11:

Acute Effects:

| | |
|-------------------|---|
| Swallowed | Not applicable. Ingestion unlikely due to form of product. Ingestion of the loose fiber from this product may irritate the gastric tract causing nausea and vomiting. |
| Dermal | Not applicable. |
| Inhalation | Not applicable. Inhalation of loose fiber may irritate the respiratory system. |
| Eye | Loose fiber may be irritating to eyes. The symptoms may include redness, itching and tearing. |
| Skin | May be irritating to skin. The symptoms may include redness, itching and swelling. Prolonged or repeated contact may cause dermatitis |



Chronic Effects:

| | |
|-------------------------------|--|
| Carcinogenicity | Not considered to be a carcinogenic hazard. Titanium oxide and Carbon black are listed as a Group 2B: Possibly carcinogenic to humans according to International Agency for Research on Cancer (IARC). |
| Reproductive Toxicity | Not applicable. |
| Germ Cell Mutagenicity | Not applicable. |
| Aspiration | Not applicable. |
| STOT/SE | Not applicable. |
| STOT/RE | Not applicable. |

SECTION 12:

This product is not hazardous to the environment

| | |
|--------------------------------------|-------------------|
| Persistence and degradability | No data available |
| Bioaccumulation | No data available |
| Mobility in Soil | No data available |
| Other adverse effects | No data available |

SECTION 13:

Disposal considerations.

Disposal methods:

Dispose according to Local Regulations.

Precautions or methods to avoid:

None known.

SECTION 14:

This product is NOT classified as a Dangerous Good for transport in NZ ; NZS 5433:2012



SECTION 15:

Regulatory information

This substance is NOT hazardous according to the Hazardous Substances (Classification) Notice 2017

SECTION 16:

Other information

Glossary

EC50 Median effective concentration.

EEL Environmental Exposure Limit.

EPA Environmental Protection Authority

HSNO Hazardous Substances and New Organisms.

LC50 Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.

LD50 Lethal dose to kill 50% of test animals/organisms.

LEL Lower explosive level.

OSHA American Occupational Safety and Health Administration.

TEL Tolerable Exposure Limit.

TLV Threshold Limit Value-an exposure limit set by responsible authority.

UEL Upper Explosive Level

WES Workplace Exposure Limit

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Building Chemistry Industry

Suit No 203, Al Manar Business park Bin Khalid Street Dammam .Kingdom of Saudi Arabia.

Email: info@bcisaudi.com Website: www.bcisaudi.com

